



- NOTES:
1. PIPING MATERIAL: PE, Carbon steel st, 304.
  2. CONNECTION TYPE: FLANGE.
  3. MANUAL VALVES SHALL BE INSTALLED AT THE INLET AND OUTLET OF THE DISC FILTER.
  4. THE DRAIN PIPE SHALL BE CONNECTED TO THE DRAINAGE SYSTEM.
  5. POWER SUPPLY: 220V/1PHASE/50HZ.
  6. CONCRETE FOUNDATION (HEIGHT: 200MM)
  7. AND EXPANSION ANCHOR BOLTS ARE SUGGESTED FOR SITE INSTALLATION.

|     |             |      |       |      |      |      |                                     |          |          |        |       |
|-----|-------------|------|-------|------|------|------|-------------------------------------|----------|----------|--------|-------|
|     |             |      |       |      |      |      | Beijing Haihao Technologies Co.,Ltd |          |          |        |       |
| 标记  | 处数          | 分区   | 更改文件号 | 签名   | DATE |      | HF-A3-5-6 DISCFILTER                | MATERIAL | QUANTITY | WEIGHT | SCALE |
| R   | 内部评审版       |      |       |      |      |      | DWG NO                              | /        | 1        |        | 1:1   |
| A   | 初步设计        |      |       |      |      |      | HF-A03-5-00-01                      |          |          |        |       |
| REV | DESCRIPTION | DESD | DATE  | APPD | DATE | APPD | DATE                                | SHEET    |          | OF     |       |